

### What is Covered:

The Manufacturer will, at its discretion, repair or replace any Product found to be defective in materials or workmanship during the 90-day warranty period. The decision to repair or replace will be made by the Manufacturer after an inspection of the defective Product.

### What is Not Covered:

This Warranty does not cover damage resulting from misuse, abuse, accidents, alterations, or improper installation. It also does not cover normal wear and tear.

### Claim Procedure:

To make a claim under this Warranty, the original purchaser must contact Tricktech at [support@tricktech.com] within the 90-day warranty period. Proof of purchase, including the date of purchase, must be provided.

### Limitation of Liability:

To the extent permitted by law, the Manufacturer's liability under this Warranty is limited to the repair or replacement of the defective Product. The Manufacturer shall not be liable for any incidental or consequential damages.

Form: S-00201



# TRICKTECH

## Tricktech Barrel Band for the Benjamin Akela

# Installation Instructions

Made in the USA | #T-101-5000201

***Before You Begin: Ensure that your Benjamin Akela is unloaded, and the magazine is removed. Always follow proper firearm safety procedures.***

### Notes: Please Read

- Clean the mating surfaces on the rifle to ensure a clean, dust and dirt-free surface to avoid the possibility of any contaminants marring or scratching the rifle.
- The Tricktech Barrel Band is manufactured with strict tolerances and is designed to restore the proper alignment of the barrel shroud and air cylinder. There may be some movement during installation and **re-zeroing of your scope IS EXPECTED.**

- **DO NOT OVERTIGHTEN.** Tighten the screws evenly by hand. Excessive pressure is not required OR recommended to hold the band in proper position or alignment. "Firm" but not "tight" is adequate and minimizes the possibility of a stripped or broken screw. Thread-lock has been pre-applied to the provided screws.

### Tools/Parts Required:

- Two (2) M3 14mm Torx® head screws (Thread-lock pre-applied)
- Tricktech Barrel Band
- Cleaning solution and lint-free cloth
- Appropriate-sized Torx® wrench (included with the Barrel Band)

## Installation Steps:

### Step 1: Gather Tools and Ensure Safety

- Gather the required tools/parts listed.
- Double-check that the rifle is unloaded, and the magazine is removed.
- Clean the mating surfaces on the rifle.

### Step 2: Position the Barrel Band

- Identify the optimal location for the Barrel Band on the free-floating barrel assembly. While this is a personal choice, ensure that the band does not interfere with the stock or air cylinder end cap.
- Test-fit the band to ensure that it can be positioned securely and aligns with the aesthetics of your rifle. The holes for the screws can be positioned on either side of the rifle, facing left or right.

### Step 3: Align and Insert Screws

- While pinching the band in its final location, insert the provided screws into the designated holes on the Barrel Band.
- Start each screw slowly and gently, making sure not to cross thread. Since thread-lock has been pre-applied, getting the screws started may require a bit more pressure than you might expect proceed slowly and be cautious not to over-tighten a thread which may be cross threaded. The thread-locked screw will offer some resistance but will be smooth while threading when properly aligned.
- Use the provided Torx® wrench to lightly tighten one screw to contact and proceed to the second screw prior to tightening the first again. Apply light pressure while alternating between screws, tightening them EVENLY.

- PRIOR to final tightening, confirm the Barrel Band is properly seated against the barrel and cylinder and in its chosen position before completely tightening with firm but not excessive pressure.

### Step 4: Final Check

- Confirm that all screws are securely tightened.
- Check the overall alignment and appearance of the Barrel Band.
- Perform a function test by shouldering the rifle and checking for any interference with moving parts.
- Ensure that the Barrel Band does not impede the normal operation of the rifle.

### Step 5: Range Test/Zero

- Take your rifle to a shooting/plinking range and RE-ZERO your optics.

If you encounter any difficulties during installation or have concerns about the Barrel Band's fitment, contact Tricktech customer support for assistance:

**support@tricktech.com**

**Always follow safety guidelines and consult your rifle's manual for specific instructions related to modifications.**

### Tricktech Barrel Band Limited Warranty

This limited warranty ("Warranty") is provided by Tricktech ("Manufacturer") for the Tricktech Barrel Band ("Product"). This Warranty is effective for a period of 90 days from the date of purchase.

#### Coverage:

The Manufacturer warrants the Product to be free from defects in materials and workmanship under normal use and service. This Warranty is limited to the original purchaser and is not transferable.